



Model STANDARD

600 L
1000 L
1500 L
2000 L



Prednosti pršilnikov Standard:

- ▶ opremljeni so z rezervoarji za èisto vodo za Pranje rok in pranje sistema
- ▶ izmet škropiva je z zrakom usmerjen poševno nazaj, kar povečuje depozit sredstva na rastlinah
- ▶ velik premer ventilatorja za veèje medvrstne razdalje
- ▶ sesalna in tlaèna filtracija
- ▶ velika vlivna odprtina z mešalcem prašnatih sredstev
- ▶ èistilec rezervoarja
- ▶ stator za simetrièni izstop zraka
- ▶ upravljanje iz kabine traktorja z enoroènim regulatorjem

Dodatna oprema:

- ▶ premiena ruda, ki sledi koloteku traktorja
- ▶ ejektorski polnilec
- ▶ elektrièni ventili
- ▶ pnevmatike Terra
- ▶ zraène lopute z dodatno šobo
- ▶ luèi za vožnjo po cesti
- ▶ èistilec embalaže



Vorteile der Gebläsespritzen STANDARD:

- ▶ zwei Reinwasserbehälter zum Verdünnen des Spritzbrüherestes, zum Durchspülen des Ausbringsystems sowie zum Händewaschen
- ▶ das Gebläse saugt die Luft von vorne an und bläst tangential durch Strömungsleitvorrichtung
- ▶ großer Ventilator für höhere Bäume
- ▶ Fernbedienung mit moderner Einhebel-Regelarmatur
- ▶ große Einfüllöffnung mit Einspülvorrichtung
- ▶ Saug- und Druckfilter
- ▶ Statorflügel für symmetrischen Luftaustritt
- ▶ Behälter-Innenreinigung

Wunschrüstung:

Elektroventile, Wasserejektor, Terra- Breitreifen, Knickdeichsel, Luftleitbleche, Beleuchtung, Kanisterreiniger.



Sprayers STANDARD have following advantages:

- ▶ Two clean water tanks for thinning the rest of the sprinkling-broth, washing the system and for hand washing
- ▶ Lateral sucking of air to reduce noise levels
- ▶ Larger ventilator capacity for spraying higher trees
- ▶ Single-handed remote control for guidance from the tractor's cabin
- ▶ Large infuse opening with the hydraulic dust mixer at the basket filter
- ▶ Suction and high pressure filter
- ▶ Stator wings for symmetric output of the air
- ▶ Rotating tank washer

Additional equipment:

Electro ball valves, water ejector, terra tires, steering tow rod, air deflectors, lighting system, can washer.



PRIPOROÈILO ZA UPORABO PRŠILNIKOV ZM 600 S, ZM 1000 S, ZM 1500 S in ZM 2000 S

- ▶ medvrstna razdalja 2,0 - 5,0 m
- ▶ višina škropljenja do 4,5 m
- ▶ površina škropljenja
 - ZM 600 S do 15 ha
 - ZM 1000 S do 20 ha
 - ZM 1500 S do 25 ha
 - ZM 2000 S do 25 ha
- ▶ vrste nasadov
 - univerzalni, za vse vrste nasadov
 - z dodatno opremo (dodatni venci in šobni nastavki za škropljenje teras), tudi za škropljenje teras

	L	L/min	bar	Ø	m³/h	m/s	kW	N°	A	B	C	kg
ZM 600 S	600	106	50	700	50.000	35	25	12	1300	1470	2770	400
ZM 1000 S	1000	106	50	700	50.000	35	25	12	1300	1470	3570	440
ZM 1500 S	1500	124	50	700	50.000	35	29	12	1350	1470	3870	500
ZM 2000 S	2000	124	50	700	50.000	35	29	12	1350	1550	4100	600



EINSATZBEREICH FÜR GEBLÄSESPRITZEN ZM 600 S, ZM 1000 S, ZM 1500 S UND ZM 2000 S

- ▶ Reihenabstand 2,0 - 5,0 m
- ▶ Kulturhöhe bis 4,5 m
- ▶ empfohlene Sprühfläche
 - ZM 600 S bis 15 ha
 - ZM 1000 S bis 20 ha
 - ZM 1500 S bis 25 ha
 - ZM 2000 S bis 25 ha
- ▶ Anlagetyp
 - universal, für alle Typen von Anlagen
 - mit Zusatzausrüstung auch für Terrassen.



USE RECOMMENDATIONS FOR ZM 600 S, ZM 1000 S, ZM 1500 S AND ZM 2000 S

- ▶ Row width 2,0 - 5,0 m
- ▶ Spraying height up to 4,5 m
- ▶ Recommended spraying area
 - ZM 600 S up to 15 ha
 - ZM 1000 S up to 20 ha
 - ZM 1500 S up to 25 ha
 - ZM 2000 S up to 25 ha
- ▶ Type of plantations
 - Universal, for all types of plantations
 - With additional equipment also for terraces.

